



PeopleLink PVC 50WS



PeopleLink PVC 50WS is a digital wireless speakerphone with the perfect audio solution for boardrooms and conference rooms. The microphones have 360-degree audio pickup capability and deliver up to 87dB of clear audio output. The echo cancellation and noise reduction features help prevent background noise and echoes from interfering with the conference.

Key Features

- **Speaker Phone:** Simultaneously uses a microphone and loudspeaker without the need for a headset/handheld unit
- **Wireless Unit:** Permits meetings to be managed with complete control and reliability
- **87dB Speaker Out:** Produces high fidelity audio quality
- **Built-in AEC, AGC and ANS:** Acoustic Echo Cancellation, Automatic Gain Control, and Acoustic Noise Suppression
- **Omni-Directional Microphone:** These microphones can pick up sound equally from all directions

General Specifications

I/O

Interface : USB 2.0 (full), 3.5mm out

Frequency Range : 2.400 GHz~2.4835 GHz

PHONE SET FEATURES

Keypad Flash : Microphone zone selection, Volume Up/Down, Microphone Mute, Speaker Mute

USER INTERFACE

USB Nos. : 1 Nos

Frequency Range : USB 2.0 B Type

Mute Indicators and Number : Yes

AUDIO TECHNOLOGY

DSP based Echo cancellaion : Yes

AUDIO FEATURES

Speaker Gain Control< 12dB

Automatic Level Control< 18dB

Built-in Microphone: 1 Nos

Microphone pickup

Range: up to 10 ft.

Audio Input:1 x USB 2.0

Noise Reduction< 16dB

Speaker Output:87dBA

Power Consumption:2.5W

Frequency Range:2.400 GHz~2.4835 GHz.

Audio Output:1 x 3.5mm Stereo Line-Out

Background Noise

Supression< 16dB

ENHANCED AUDIO FEATURES

Automatic Echo Cancellation : Yes

Automatic Gain Control : Yes

Noise Reduction : Yes

Full Duplex : Yes

Non Linear Processing : Yes

Automatic Level Control : Yes

RECOMMENDED ROOM CONDITIONS

Reverberation Time : <0.5 second

Noise Level : <48 dBA

ELECTRICAL

Power Operating : USB bus powered (DC 5V/500mA)

Temperature : 0°C to 40°C

Environmental Humidity : 20-85% (RH)

PHYSICAL CHARACTERISTICS

PackageDimension :155 mm x 148 mm x 37 mm (L x W x H) (1 Unit)

Net Weight : 312 grams

Gross Weight : 660 grams (Package)

PACKING INFORMATION

USB Cable (1.8 mtr.), User Manual, Wireless Dongle

APPLICATION




Room type : Board room Or conference room

Room size : 40Ft x 30Ft

Capacity table shape : 10 to 24 seater
Recommended for Oval or U shape table




Application Scenarios

Huddle room**Huddle room****Meeting room**

Disclaimer:- Room setup diagrams provided for reference only. Actual room setup and size may vary as per requirements.

Connectivity



Ordering Information

PeopleLink PVC 50WS

: PPU-PVC-AD-50WS

LEARN MORE

For more information on **PVC 50WS** [Click Here](#)

SALES AND INQUIRIES

Global Headquarters

Q3-A3, 10th Floor Cyber Towers,
HITEC City, Hyderabad,
Telangana 500081, **India**
Phone: **+91 9100123013**
Email: **vc@peoplelinkvc.com**

International Contact Numbers

USA: +1 669-696-8383
Australia: +61 370 037070
France: +33 6 80 75 26 42
Middle East: +966 5300 19292
UK: +44 20 4571 5454

Tech Support

Toll Free: 1800 208 3399
customersupport@peoplelinkvc.com

UAE: +971 559-002093
Canada: +1 647-945-7373
Malaysia: +(6)018-2872188
New Zealand: +64-9-802-4666
Africa: +254 722 619 314