



[CLICK TO WATCH VIDEO](#)

UVC 15B

PeopleLink UVC 15B microphone are used in board and conference rooms. The compact design helps in easy portability and storage. The 360 degree pan audio pickup allows the microphone to capture audio from every corner of the room. The 89 dB audio output is completely free from any background noise interference or echoes..It can be use through wire or wireless by using bluetooth, in-bulit battery that can sustain up to 6 hours of continuous conference.



Speaker phone: Simultaneously uses a microphone and loudspeaker without the need for a headset/handheld unit



Digital wired conference unit: Permits meetings to be managed with complete control and reliability



3 Bi-directional microphone (360 degree): These microphones can pick up sound equally from all directions



89db speaker out: Produces high fidelity audio quality



Built in AEC, AGC and ANS: Acoustic Echo Cancellation, Automatic Gain Control, and Acoustic Noise Suppression



[CLICK TO VISIT WEBPAGE](#)



NFC & Bluetooth: Near-field communication (NFC) and Bluetooth enables electronic devices to establish communication in near proximity



3.5mm jack audio out: For composite video and audio output

Applications

- Area of application: Board room or Conference room
- Ideal Room size: 12ft by 12ft
- Capacity: 8 to 10 seater
- Shape of table: Recommended for oval shape table



[CLICK TO WATCH VIDEO](#)

Specifications

UVC 15B

I/O

Interface USB 2.0 (full), 3.5mm In/out

Frequency Range 30Hz to 16KHz

PHONE SET FEATURES

Keypad Flash Microphone zone selection, Volume Up/Down, Microphone Mute, Speaker Mute,

USER INTERFACE

USB Nos. 1 Nos
 USB type USB 2.0 B Type
 NFC Yes

Mute Indicators and Number Yes
 Bluetooth Yes

AUDIO TECHNOLOGY

DSP based Echo cancellaion Yes

AUDIO FEATURES

Speaker output	89 dB	Microphone pickup range	upto 8 ft
Frequency Range	30Hz to 16KHz	Audio Input	1 x USB 2.0 & 3.5mm Jack
Built-in Microphones	3 Nos	Audio Output	1 x 3.5mm Stereo Line-out

ENHANCED AUDIO FEATURES

Automatic Echo Cancellation	Yes	Non Linear Processing	Yes
Automatic Gain Control	Yes	Automatic Level Control	Yes
Noise Reduction	Yes		
Full Duplex	Yes		

ELECTRICAL

Power	USB bus powered (DC 5V)	Power Consumption	300mAh Max
Operating Temperature	5°C to 40°C		

PHYSICAL CHARACTERISTICS

Dimension	140 mm x 32 mm (Dia x H)	Gross Weight	500 grams
-----------	--------------------------	--------------	-----------

PACKING INFORMATION

Contains	6 Ft USB Cable, Protective Travel Case, User Manual
----------	---

ORDERING INFORMATION

PeopleLink UVC 15B	PPU-PVC-UV-15B
--------------------	----------------

APPLICATION

Room type	Board room Or conference room	Capacity	8 to 10 seater
Room size	12 Ft X 12 Ft	Table shape	Recommended for Oval shape table

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City, Madhapur, Hyderabad - 500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070 Africa : +27-10-5001977 Canada : +1-647-4964195
UK : +44-20-35190197 Australia: +61-29-0988367 Middle East : +973-1-6199342

Follow us:       www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (if any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.