



 [CLICK TO WATCH VIDEO](#)

iCam WHD 1080 12X USB_EN

PeopleLink iCam WHD 1080 are cameras for board rooms offering easy connectivity with laptops/PC through USB ports. The Pan/tilt features present in the devices allow a wider angle coverage. HD video quality with real time, face-to-face experience through the powerful 12x optical zoom some more unique offering of these cameras. They can also adjust the brightness automatically according to the lighting condition of the room ensuring clear video.



True HD 1080p @ 60 FPS: This camera offers recordings with very vivid clarity (True HD) at a resolution of 1080p @ 60 frames per second (FPS)



12x Optical zoom: Optical zoom is a true zoom lens that produces much better-quality images than digital zoom which performs in-camera image processing



FOV 72.5° degree: The camera has a wide field of view (FOV), the area covered by the camera, of 72.5° degrees



Pan tilt zoom: Pan-tilt-zoom (PTZ) type of cameras enable the user to control the movement and position of the lens. Panning refers to the lens's horizontal movement while tilting describes its vertical movement



IR remote controllable: Remotes with infrared light can be used to reliably control this camera



RS-232: RS-232 MISCA to control the PTZ functions of the camera remotely



 [CLICK TO VISIT WEBPAGE](#)



Applications

- "Area of application: Board room
- Capacity: 30 to 60 seater
- Shape of the room: Rectangular
- Bright /Dark room: Auto brightness adjustment
-



[CLICK TO WATCH VIDEO](#)

Specifications

iCam WHD 1080 12X USB

GENERAL SPECIFICATIONS

Camera

Video System	:	1080p/60, 720p/60
Sensor	:	1/2.8", CMOS, Effective Pixel: 2.07M
Scanning Mode	:	Progressive
Lens	:	12x, f3.5mm ~ 42.3mm, F1.8 ~ F2.8
Digital Zoom	:	16x
Minimal Illumination	:	0.5 Lux @ (F1.8, AGC ON)
Shutter	:	Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K_1, 6500K_2, 6500K_3, One Push, Manual
Backlight Compensation	:	support
Digital Noise Reduction	:	2D&3D Digital Noise Reduction
Video S/N	:	≥55dB

GENERAL SPECIFICATIONS

Camera

Horizontal Angle of View	:	72.5° ~ 6.9°
Vertical Angle of View	:	44.8° ~ 3.9°
Horizontal Rotation Range	:	±170°
Vertical Rotation Range	:	-30° ~ +30°
Pan Speed Range	:	1.7° ~ 100°/s
Tilt Speed Range	:	0.7° ~ 28°/s
H & V Flip	:	Support
Image Freeze	:	Support
Number of Preset	:	255
Preset Accuracy	:	0.1°

USB Features

Operate System	:	Windows 7, Windows 8, Windows 10 Mac OS X, Linux
Color System / Compression	:	YUV 4:2:2 / H.264 / MJPEG
Video Format	:	USB3.0: 1080p/60, 1080p/50, 1080p/30, 1080p/25, 720p/60, 720p/50, 720p/30, 720p/25 USB2.0: 1080p/30, 1080p/25, 1080p/15, 1080p/10, 720p/30, 720p/25, 960x540p/30, 960x540p/25, 640x360p/60, 640x360p/50
Audio on USB	:	Support
USB Video Communication Protocol	:	UVC 1.0 ~ UVC 1.5
UVC PTZ	:	Support

Input/Output Interface

USB Interface	:	1xUSB3.0: Type B female jack
Audio Interface	:	1-ch: 3.5mm Audio Interface, Line In
Communication Interface	:	1xRS232 In: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA/Pelco-D/Pelco-P 1xRS232 Out: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA network use only 1xRS485: Share with RS232 Out, Max Distance: 1200m, Protocol: VISCA/Pelco-D/Pelco-P
Power Jack	:	JEITA type (DC IN 12V)

GENERAL SPECIFICATIONS

Generic Specifications

Input Voltage	: DC 12V
Current Consumption	: 1.0A (Max)
Operating Temperature	: -10°C ~ 40°C (14°F ~ 104°F)
Storage Temperature	: -40°C ~ 60°C (-40°F ~ 140°F)
Power Consumption	: 12W (Max)
MTBF	: >30000h
Size	: 128.5x118x156.2mm
Net Weight	: 0.91K g

Ordering Information

Contents

Camera, Power Adapter, IR remote, USB 3.0 Cable, User Manual and Serial to Visca cable.

PeopleLink iCam WHD 1080 USB

Part code

: PPU-PVC-PC3-108P-12X

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,
Madhapur, Hyderabad -500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070
UK : +44-20-35190197

Africa : +27-10-5001977
Australia : +61-29-0988367

Canada : +1-647-4964195
Middle East : +973-1-6199342

Follow us:       www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks /products mentioned (if any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.