



PeopleLink UVC 25

PeopleLink UVC 25 speakerphones are used in board room and conference rooms. They can be easily connected with VC peripherals through USB wire. The omni-directional in-built microphones helps in capturing 360 degree audio within a room and delivers 85 dB of clear output without any background noise or echoes.

Product Features

- Easy to carry, small and medium-sized meetings will be launched at any time
- HD, full duplex audio solution
- Microphone dynamic speech enhancement technology
- Adaptive high-definition amplification technology
- The 3.5mm interface can be used for docking mobile phones or other analog devices.
- support USB
- Low power consumption design
- 360 degree omni directional pickup, plug and play
- The inductive button design is more dust-proof and more durable.

Product Specifications

Applicable scenarios: personal office for business people, small meeting rooms, carry- on travel, etc.

Plug and play: Portable USB omnidirectional microphone (SpeakerPhone), which can be quickly connected to a computer or mobile phone via USB to join the conference, simple and convenient, plug and play.

Microphone array: Built- in four- microphone array, 360° omnidirectional pickup, full- duplex audio technology, can better pick up and call at a long distance, more accurate listening position, intelligent noise reduction, automatic gain, echo cancellation.

- Support for emergency power failure of mobile phones and other devices via USB, reverse charging, multiple circuit protection, and energy at your fingertips.
- The bar- shaped RGB indicator light, with a variety of colors, allows users to easily identify the current power, volume, incoming call, mute and other working status of the product, and the operation is convenient and simple.
- Small and exquisite appearance, easy to put in your pocket, convenient to carry.

Product Specifications

microphone

Distance	:	6m
Frequency response	:	50-16900 Hz
Directivity	:	Omnidirectional

Speaker

Frequency response	:	20-20kHz
Volume	:	85dBA

Audio frequency

Full duplex echo cancellation	:	support
Noise suppression	:	support
Gain control	:	support
Echo tail length	:	300ms

Connection mode

Network	:	1 x USB Data Communication 1 x 3.5mm audio interface
Key	:	Induction button

Environment condition

Power supply	:	USB: 5V DC @ 450 mA Maximum
Rechargeable battery	:	NA
Support operation	:	windows XP/Vista/7/8/10
Working temperature	:	0°-40°C
Storage temperature	:	-30°-55°
Relative humidity	:	20-85%(non-condensing)

Product Specifications

Meeting capacity

Covering area	:	15-30m ²
Number of participants	:	6-12 person

Packing

Telephone size (R x H)	:	75mm x 30mm
weight	:	0.48kg
Packing catalogue	:	Quick User Guide, USB Cable, Omnidirectional microphone

Warranty

1 year warranty

Ordering Information

PeopleLink UVC 25

Part code : PPU-PVC-UVC-25

GLOBAL HEADQUARTERS

Q3-A3, 10th Floor, Cyber Towers, Hitech City,
Madhapur, Hyderabad - 500 081 (India)
Phone: +91 (40) 66903959 / 60
Email: vc@peoplelinkvc.com

INTERNATIONAL CONTACT NUMBERS

USA : +1-321-2163070	Africa : +27-10-5001977	Canada : +1-647-4964195
UK : +44-20-35190197	Australia: +61-29-0988367	Middle East : +973-1-6199342

Follow us:       www.peoplelinkvc.com/social-presence

DISCLAIMER: PeopleLink Unified Communications Pvt. Ltd., All rights reserved. All third party trademarks / products mentioned (if any) are the property of their respective owners. Product Images are for illustration purpose only. Actual product may vary due to product enhancements. All specifications are subject to change without notice; system specifics may vary.

PeopleLink Public Document | PeopleLink Unified Communications Pvt. Ltd. | ISO 9001:2015 & ISO/IEC 27001:2013 Certified Company.