



PeopleLink Cascade 4C+



PeopleLink Cascade 4C+ Cascade is a conference audio controller. The 4C can be connected with an active speaker interface and 4 omnidirectional microphones based on a 2.4G wireless cascade. It also supports local amplification of wireless handheld microphones widely used in large conferences. It can also be used generally in Conference rooms and entertainment venues.

Intelligent Audio Processing:

Adopting the latest audio voice processing technology, including digital audio processing, dynamic noise reduction processing, industry-leading 384ms echo cancellation, full-duplex voice calls, 360° omni-directional pickup, etc. The effective pickup radius of a single omnidirectional microphone can reach 2m. Two-way, natural, and smooth meetings can be conducted at the same time, giving users a high-quality.

Key Features

- Support external active speakers
- Supports conference communication software such inVC, skype, zoom etc.
- Removable wireless omni directional microphone



General Specifications

Interface

- B type USB interface
- 6.5 mm audio jack
- Antenna interface
- DC power interface

Wireless Omnidirectional Microphone

- Audio bandwidth is 100-16KHz
- Sensitivity: -38 dB 94dB
- SPL@1KHz Signal to noise ratio: 65dB
- 94dB SPL@1KHz, A-weight

Audio Characteristics

- Digital Audio Processing
- 384 ms Echo Cancellation technology
- Intelligent Dynamic Noise Reduction
- Full Duplex 360° pickup range
- Effective pickup range - 3 to 4 meters

Computer System Required

Windows 7 / Windows 10 / MacOS

Power Supply

- Host power adapter -12V2A
- Slave power adapter -5V/500mA

Button on mics

- Microphone mute button
- Speaker mute button
- Volume up/down button
- Slave switch button

Master LED light Status

Master red light is always on: under normal work

The speaker status indicator on master is on green:
Under normal work

The speaker status indicator light on master is on red:
Speaker mute

Slave Mics LED Light Status

Normal work: the green light is always on

Mute microphone: red light is always on

Low power: the red light of the speaker flashes

Volume adjustment: the mic green indicator flashes

Not connected normally: the green light flashes

Environmental Requirements

Temperature: 5°~44°

Humidity: 20~85% (no condensation)

Noise Level: <48db

Storage Temperature: -10°~55°




Product Parameter

Size: Master - 267*145*51mm
Single mic - 110*110*25mm

Weight: Master - 1044g
Single mic: 236g


Color: Business black

Application Scenarios



Disclaimer:- Room setup diagrams provided for reference only. Actual room setup and size may vary as per requirements.

Connectivity



Ordering Information

PeopleLink Cascade 4C+

: PPU-PVC-AD-50WS-4C+

LEARN MORE

For more information on Cascade 4C+ [Click Here](#)

SALES AND INQUIRIES

Global Headquarters

Q3-A3, 10th Floor Cyber Towers,
HITEC City, Hyderabad,
Telangana 500081, **India**
Phone: **+91 9100123013**
Email: **vc@peoplelinkvc.com**

International Contact Numbers

USA: +1 669-696-8383
Australia: +61 370 037070
France: +33 6 80 75 26 42
Middle East: +966 5300 19292
UK: +44 20 4571 5454

Tech Support

Toll Free: 1800 208 3399
customersupport@peoplelinkvc.com