



V 1.0 - 032024

PeopleLink Fusion AIO16



PeopleLink Fusion 16 Webcam is a high-definition 1080p webcam is designed to take your virtual video meetings, webinars, gaming and online collaborations to the next level. The all in one HD Webcam with Speaker and Microphone has 90° FOV, 4X Digital Zoom, Ultra fast auto focus, Privacy Cover and USB HD Computer Web Camera. Plug and Play to connect with Zoom/Skype/Teams Conferencing and Video Calling, Gaming, Streaming, Online Classes and webinars.

- **Built-in Physical Privacy Masking** : Equipped with an integrated sliding privacy cover to security the privacy.
- **Low illumination** : The new CMOS image sensor with ultra-high SNR can effectively reduce the image noise under low illumination. The application of 2D and 3D noise reduction algorithm greatly reduces the image noise even under the condition of ultra-low illumination, it keeps the picture clean and clear, and the SNR of image is as high as 55dB.
- **Easy Installation** : The standard damped rotary support compatible with almost 100% display devices on market, easy to install, stable and reliable.

Key Features

- **Integrated Bionics Design to Simplify the Complex** : Integrated high-definition camera with high-sensitivity omnidirectional microphone, full-frequency speaker three-in-one design, plug and play, reducing wiring and making video communication easy and simple. The unique bionic design allowing you to get excellent audio-visual effects in video communications.
- **1080P Full HD Ultra-wide-angel without Distortion** : Support 1080P High Definition, Provide image Encoding Output up to 1080@30fps/25fps and Downward Compatible with 720P and Other Resolutions. The Wide and Horizontal Field of View up to 90°
- **Full-frequency Speaker** : Speakers with Ducted sound Cavity, The Treble is Clear and Penetrating and The Bass is Naturally Surging to Providing an Extraordinary Sound Effect.
- **Audio 3A Algorithm** : The built-in audio 3A algorithm (AEC/AGC/ANS) and full-duplex mode adjust the high and low volume of the balance and suppress the noise automatically while in voice collection to meet your needs for loud and clear communication.
- **TOF High-speed Focusing** : The laser-assisted focusing instrument with advanced auto focusing algorithm to realize high-speed and accurate auto focusing.
- **Landscape and Portrait Mode** Support one-key landscape and portrait switching output to meet the needs of various landscape and portrait live scenes.
- **e-PTZ** : No mechanical rotating device needed for more accurate rotation accuracy, no noise, more reliable and durable, support 4x digital zoom.

General Specifications

Camera

Sensor : 1/2.8 inch, CMOS, Effective Pixel: 2.07M;

Scanning Mode : Progressive

Type of Lens Mount : M12

Lens : Focus: f=2.8mm

Horizontal FOV: 90°

AF : Support TOF

Minimum Illumination : 0.5 Lux @ (F2.0, AGC ON)

Shutter Speed : 1/30s ~ 1/10000s

White Balance : Auto, Manual, VAR

Camera Stand : Standard Damped Rotary Support

Physical Privacy Security : Support

Digital Noise Reduction : 2D&3D Digital Noise Reduction

Backlight Compensation : Support

Digital Zoom : 4X

Audio Features :

Audio 3A Algorithm : Support AEC/AGC/ANS

Speaker : 82 dB SPL at 0.5 m

Microphone : Omnidirectional Microphone,

Sensitivity:-30±2dB

I/O Interface :

USB Interface : 1 x USB 2.0: Type-A

USB Features :

Operate System :

Windows® 7 (only 1080P and below supported),
Windows 8.1, Windows 10 or Higher, MacOS™ 10.10
or higher, Google™ Chromebook™ Version
29.0.1547.70 or Higher, Linux (support UVC)

Hardware Requirements :

2.4 GHz Intel® Core 2 Duo CPU or higher, 2 GB RAM
or more
USB 2.0 interface

Color System / Compression :

YUY2 / H.264 / MJPEG

Video Resolution :

1080P@30fps/25fps, 720P@30fps/25fps,
960x540P@30fps/25fps,
640x360P@30fps/25fps

USB VC Protocol : UVC 1.1

UAC : Support

UVC PTZ Control : Support (EPTZ)

General Specifications :

Input Voltage : 5V (USB Power Supply)

Input Current : 0.5A

Operating Temperature : 0° C ~ 40° C




Storage Temperature : -40° C ~ 60° C

Power Consumption : 2.5W(Max.)

Dimensions : 121mm x 32mm x 31mm (Bracket not included)


Net Weight : 139g

Application Scenarios



Disclaimer:- Room setup diagrams provided for reference only. Actual room setup and size may vary as per requirements.

Mounting Options



Ordering Information

Part code : PPU-PVC-WC-I9+

LEARN MORE

For more information on Fusion 16 [Click Here](#)

SALES AND INQUIRIES

Global Headquarters

Q3-A3, 10th Floor Cyber Towers,
HITEC City, Hyderabad,
Telangana 500081, **India**
Phone: **+91 9100123013**
Email: **vc@peoplelinkvc.com**

International Contact Numbers

USA: +1 669-696-8383
Australia: +61 370 037070
France: +33 6 80 75 26 42
Middle East: +966 5300 19292
UK: +44 20 4571 5454

Tech Support

Toll Free: 1800 208 3399
customersupport@peoplelinkvc.com